



### Specifications

Brand: 3M  
 Designation: VHB 9473 PC transparent  
 Adhesive system: modified acrylic  
 Thickness: 250 (without liner)  
 Liner: Poly Coated Tan Paper white  
 with brand name  
 3M VHB green  
 Temperature resistance: 150° C

### BIADHESIVE NOT ASSEMBLED

RIF.	Q.TY	DRAWING	DESCRIPTION					
1	1	2_010_00051	FRONT PANEL ITOUCH GLASS					
2	1	2_010_00054	ITOUCH FRAME ADHESIVE					
from 0.5 to 3	from 3 to 6	from 6 to 30	from 30 to 120	from 120 to 400	Sheet:			
± 0.1	± 0.1	± 0.2	± 0.3	± 0.5	1			
Scale:	Drawed:	Checked:	Date:	Material:	Process:			
1:1	R.N.	R.N.	20/03/2023					
		The present drawing cannot be reproduced or communicated to 3rd parties, even partially, without the authorization of ITALTRONIC Srl. Italconic reserves to protect its own rights according to the law.			Weight:			
Dimension in mm		Derived from:			Cod. Mold:			
--		--			gr			
<b>italtronic</b> enclosures for electronics italtronic.com								
Description: PANNELLO FRONTALE ITOUCH IN VETRO C/BIADESIVO FRONT PANEL ITOUCH GLASS WITH ADHESIVE								
Drawing nr.: <b>3_010_00025</b>								
Rev.: <b>00</b> <b>A4</b>								

### General information:

- Workpiece zero point for mechanical processing
- Minimum recommended radius for machining = R1.0 mm